



K008-3



SPECIFICATIONS

Specifications

Model		K008-3		
Type of tracks		Rubber		
Engine	Model		Kubota D722-E3	
	Output (SAEJ 1995 gross)	HP (kW)/rpm	10.3 (7.7) / 2050	
	Output (SAEJ 1349 net)	HP (kW)/rpm	10.1 (7.5) / 2050	
	Displacement	cu.in. (cc)	44 (719)	
	Overall length	ft.in. (mm)	9'0" (2750)	
Dimensions	Overall height	ft.in. (mm)	7'4" (2230)	
	Overall width	ft.in. (mm)	2'10" (860) / 2'4" (700)	
	Min. ground clearance	in. (mm)	5.9" (150)	
	Pump capacity	gpm. (ℓ /min)	5.55 (21.0)	
Hydraulic system	Auxiliary hydraulic flow		gpm. (ℓ /min)	5.55 (21.0)
	Max. breakout force	Bucket	lbs. (kgf)	2200 (1000)
		Arm	lbs. (kgf)	1010 (460)
Drive system	Travel speed		mph (km/h)	1.2 / 2.5 (2.0 / 4.0)
	Max. traction force		lbs. (kgf)	1695 (770)
	Tumbler distance		ft.in. (mm)	2'11" (900)
	Crawler length		ft.in. (mm)	4'0" (1230)
	Shoe width		in. (mm)	7.1" (180)
	Ground contact pressure		psi (kgf/cm ²)	3.55 (0.25)
Swing system	Unit swing speed		rpm	8.3
	Boom swing angle	Left	degree	55
		Right	degree	60
Blade	Dimensions	Width	ft.in. (mm)	2'4" / 2'10" (700 / 860)
		Height	in. (mm)	7.9" (200)
	Max. lift above ground		in. (mm)	7.9" (200)
	Max. drop below ground		in. (mm)	7.1" (180)
Hydraulic oil (reservoir/system)		gpm. (ℓ /min)	3.30 / 4.49 (12.5 / 17.0)	
Fuel reservoir		gpm. (ℓ /min)	3.17 (12.0)	
Operating weight				
Including operator's weight 175 lbs.		lbs.(kgf)	2200 (1000)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt for almost all applications.

DIMENSIONS

